

# **Wide Area Augmentation System Offline Monitoring Quarterly Report**

**1 April 2013 - 30 June 2013**

**Prepared for:**

**Federal Aviation Administration**

**Prepared by:**

**Satellite Operations Group AJW-B2  
and  
WAAS Engineering Team AJW-14B**

April 10, 2014

## Executive summary

The Wide-Area Augmentation System (WAAS) Engineering Team (AJW-14B) and the Satellite Operations Group (AJW-B2) were tasked with monitoring WAAS to ensure that the integrity requirements were maintained throughout the quarter. This report contains data collected and analyzed between April 1, 2013 and June 30, 2013. These requirements are defined in Section 3.3 of Algorithm Contribution to Hazardous Misleading Information (HMI) (A014-011). Data is collected from the WAAS network and stored at the WAAS Support Facility (WSF) at the Mike Monroney Aeronautical Center (MMAC) in Oklahoma City, OK.

The primary evidence that WAAS meets the top level system integrity requirements relies on a mathematical proof supported by a comprehensive analysis of empirical data. The foundation of the proof is built upon a set of carefully constructed assertions. Some assertions require periodic monitoring to ensure that the physical environment has not changed or degraded in a manner that would invalidate the claim. Certain satellite failure modes which have *a priori* probabilities associated with them must be detected and corrected in a reasonable amount of time to limit the user's exposure to the failure. The following assertions are monitored as called for in the Algorithm Contribution to HMI document:

1. Code-Carrier Coherence (CCC)
2. Code-Noise and Multipath (CNMP)
3. Signal Quality Monitoring (SQM)
4. Satellite Clock Run-off
5. Iono Threats
6. Ephemeris Monitoring

Additional monitoring criteria have been added to the original list. These additional monitoring criteria include Wide-area Reference Station (WRS) antenna positions, L1L2 bias levels, missed WAAS user messages, monitor trips, CNMP resets, accuracy, Geosynchronous Earth Orbit (GEO) CCC, and Space Weather. This report will also include major anomalies that occurred during the time period covered in this report. Table 1 is a summary of the criteria that were monitored for this report.

<b>Integrity monitoring</b>	
CCC	All metrics below threshold
CNMP	Two daily sigma overbound failures
SQM	All metrics below threshold
Satellite clock run-off	No run-off events
Iono threat model	Days of interest: 2013-06-01 2013-06-28 2013-06-29
<b>Availability monitoring</b>	
	SVM currently under development
<b>Continuity monitoring</b>	
System monitoring trips	0 CCC trips in the field 2 CCC trips in the W3SP runs. Under investigation. For more information see anomalies WAAS00120089 and WAAS00120090. 38 L1L2 trips on ZDC and ZTL, and 37 on ZLA 7 WRE <sub>bias</sub> trips
Missed messages	CRW (PRN-135) - 18 CRE (PRN-138) - 55 AMR (PRN-133) - 21
<b>External monitoring</b>	
Antenna positioning	All sites within allowance
<b>Anomaly Investigations</b>	
	WRE Bias Trips at MPR Instability on the L1 loopback path at HDH GUS site

**Table 1:** Monitor summary

# Forward

The scope of this document is limited to analysis performed on data extracted from the WAAS system, or on data that would directly affect the WAAS system. Moreover, the target audience is the Federal Aviation Administration (FAA) WAAS management as well as the engineers that support the WAAS program. This includes (but is not necessarily limited to) federally employed personnel, contractors, sub-contractors, and other FAA WAAS Integrity Performance Panel (WIPP) support members.

The data and information contained in this document is not for general use, as it may contain unexplained anomalies and/or data which may lead to unsupported conclusions. Any dissemination and interpretation of this data should be coordinated with the appropriate management.

# Table of contents

<b>1</b>	<b>Introduction</b>	<b>8</b>
1.1	The definition of offline monitoring . . . . .	8
1.2	Elements of system monitoring . . . . .	8
1.2.1	Integrity . . . . .	8
1.2.2	Availability . . . . .	8
1.2.3	Continuity . . . . .	9
1.2.4	Accuracy . . . . .	9
1.2.5	External monitoring . . . . .	9
<b>2</b>	<b>Integrity monitoring</b>	<b>10</b>
2.1	Code-noise and multipath . . . . .	10
2.2	Code-carrier-coherence . . . . .	13
2.2.1	CCC integrity tables . . . . .	13
2.2.2	Quarterly time-series plot of CCC GEO metric . . . . .	13
2.3	Signal Quality Monitoring . . . . .	14
2.4	Iono threat model . . . . .	16
2.4.1	Daily percentage of $\text{Chi}^2$ values $> 1$ . . . . .	16
2.4.2	Days of interest . . . . .	20
<b>3</b>	<b>Availability monitoring</b>	<b>21</b>
3.1	Service volume model . . . . .	21
<b>4</b>	<b>Continuity monitoring</b>	<b>22</b>
4.1	System monitoring trips . . . . .	22
4.2	CCC statistics and monitor trips . . . . .	22
4.3	WRE thread switches . . . . .	24
4.4	List of missed messages . . . . .	24
4.4.1	CRW (PRN-135) Events . . . . .	24
4.4.2	CRE (PRN-138) Events . . . . .	25
4.4.3	AMR (PRN-133) Events . . . . .	25
4.5	CNMP resets . . . . .	27
4.6	Satellite clock run-off monitoring . . . . .	27
<b>5</b>	<b>Accuracy monitoring</b>	<b>28</b>

<b>6</b>	<b>External monitoring</b>	<b>29</b>
6.1	Antenna phase center positions . . . . .	29
6.2	Ephemerides monitoring . . . . .	29
6.3	Space weather monitoring . . . . .	34
6.3.1	Planetary A-K indices . . . . .	34
6.4	GEO CCC signal quality analysis (GSQA) . . . . .	35
<b>7</b>	<b>Anomaly investigation</b>	<b>37</b>
7.1	Major Anomalies . . . . .	37
<b>8</b>	<b>Materials and methods</b>	<b>38</b>
8.1	Code-carrier-coherence . . . . .	38
8.2	Antenna positioning . . . . .	38
8.3	Satellite clock Run-off monitoring approach . . . . .	39
8.4	Ephemerides Monitoring Approach . . . . .	39
8.5	Iono threat model monitoring approach . . . . .	39
8.6	Code-noise and multipath . . . . .	40
8.7	GEO CCC signal quality analysis (GSQA) . . . . .	40
8.7.1	Data . . . . .	40
8.7.2	Methods . . . . .	40
<b>9</b>	<b>Supplemental material</b>	<b>41</b>
9.1	Iono threat model defined regions . . . . .	41
9.2	Code-noise and multi path . . . . .	41
9.2.1	Analysis of poor performing sites . . . . .	41
9.3	Equations . . . . .	43
9.3.1	Code-carrier-coherence . . . . .	43
9.3.2	Code-noise and multipath . . . . .	43
9.4	Tables . . . . .	44
9.4.1	Code-carrier-coherence . . . . .	44
9.4.2	WRE listing . . . . .	45
9.4.3	Space vehicle designators . . . . .	46
9.5	References . . . . .	47
9.6	GEO CCC signal quality analysis (GSQA) . . . . .	48
9.7	L1L2 bias levels . . . . .	52
9.7.1	Satellites from CP1 . . . . .	52
9.7.2	Satellites from CP2 . . . . .	53
9.7.3	WREs from CP1 . . . . .	54
9.7.4	WREs from CP2 . . . . .	55
<b>A</b>	<b>Assertions</b>	<b>56</b>
A.1	Code-carrier-coherence . . . . .	56
A.2	Code-noise and multipath . . . . .	56
A.3	Antenna positioning . . . . .	56
A.4	Iono threat model . . . . .	56
A.5	Satellite Clock Runoff . . . . .	56

<b>B Coding standards and guidelines</b>	<b>57</b>
B.1 Introduction . . . . .	57
B.2 Integrity standards for MATLAB . . . . .	57
B.3 HMI/OLM coding standards . . . . .	58
B.4 File naming conventions . . . . .	59
B.5 OLM file formats . . . . .	59
B.5.1 Histogram files . . . . .	60
B.5.2 Statistics files . . . . .	60
B.5.3 Time-series files . . . . .	61
B.5.4 Quantity files . . . . .	61
B.5.5 Quarterly files . . . . .	61
B.6 Histogram slicing and bin requirements . . . . .	61
B.7 OLM process and procedures . . . . .	62
B.7.1 Schedule and meetings . . . . .	62
B.7.2 Data processing . . . . .	63
B.7.3 Tool strategy . . . . .	63
B.7.4 Tool builds . . . . .	63
<b>C Acronyms and abbreviations</b>	<b>65</b>

# List of Figures

2.1	Aggregate CNMP Delay . . . . .	10
2.2	Aggregate CNMP Ionospheric Free PseudoRange (IFPR) . . . . .	11
2.3	Aggregate CNMP Range Domain for the L1 frequency (RDL1) . . . . .	11
2.4	Daily GPS CNMP Aggregate zero-centered sigma overbound values . . . . .	12
2.5	Time-series graph of CCC GEO metrics . . . . .	13
2.6	Time-series graph of GEO SQM metrics . . . . .	14
2.7	Time-series graph of GPS SQM max metrics 1-4 . . . . .	15
2.8	Alaska region daily % Chi <sup>2</sup> values >1 taken from ZDC . . . . .	16
2.9	Canada region daily % Chi <sup>2</sup> values > 1 taken from ZDC . . . . .	17
2.10	Equatorial region daily % Chi <sup>2</sup> values > 1 taken from ZDC . . . . .	17
2.11	CONUS region daily % Chi <sup>2</sup> values > 1 taken from ZDC . . . . .	18
2.12	West mid-latitude region daily % Chi <sup>2</sup> values > 1 taken from ZDC . . . . .	18
2.13	East mid-latitude region daily % Chi <sup>2</sup> values > 1 taken from ZDC . . . . .	19
4.1	Count of all days with switches . . . . .	24
4.2	Time on C thread . . . . .	25
4.3	Missed messages . . . . .	26
6.1	Q2 2013 Plot of Cross-Track Ephemeris Deltas between NGS and CORS Ephemeris . . . . .	30
6.2	Q2 2013 Plot of In-Track Ephemeris Deltas between NGS and CORS Ephemeris . . . . .	32
6.3	Q2 2013 Plot of Radial Ephemeris Deltas between NGS and CORS Ephemeris . . . . .	33
6.4	Planetary K <sub>p</sub> values . . . . .	34
9.1	Chi <sup>2</sup> region map . . . . .	41
9.2	Long-term fractional coherence (CC) for PRN 135 . . . . .	48
9.3	Short-term fractional coherence (CC) for PRN 135 . . . . .	48
9.4	Long-term fractional coherence (CC) for PRN 138 . . . . .	49
9.5	Short-term fractional coherence (CC) for PRN 138 . . . . .	49
9.6	Long-term code-carrier coherence (CCC) for PRN 135 . . . . .	50
9.7	Short-term fractional coherence (CC) for PRN 135 . . . . .	50
9.8	Long-term code-carrier coherence (CCC) for PRN 138 . . . . .	51
9.9	Short-term fractional coherence (CC) for PRN 138 . . . . .	51
9.10	L1l2 bias for all PRNs from CP1 . . . . .	52
9.11	L1l2 bias for all PRNs from CP2 . . . . .	53
9.12	L1l2 bias for all WREs from CP1 . . . . .	54
9.13	L1l2 bias for all WREs from CP2 . . . . .	55

# List of Tables

1	Monitor summary . . . . .	1
2.1	CCC integrity statistics (normalized to MERR value) . . . . .	13
2.2	Days when the % of $\text{Chi}^2 > 1$ exceed the threshold value . . . . .	20
4.1	System monitoring trips . . . . .	22
4.2	Reported CCC trips . . . . .	22
4.3	CCC metric statistics (unnormalized) . . . . .	23
4.4	CCC continuity statistics (normalized to trip threshold) . . . . .	23
6.1	Q2 2013 Number of Outliers for each GPS PRN . . . . .	31
6.2	GSQA performance summary . . . . .	36
8.1	Threat model regions and threshold settings . . . . .	39
9.1	Poor performing WREs for CNMP . . . . .	42
9.2	CCC trip thresholds per UDRE index . . . . .	44
9.3	WRE listing . . . . .	45
9.4	GEO satellite information I . . . . .	46
9.5	GEO satellite information II . . . . .	46
B.1	Data histogram bin requirements . . . . .	62
B.2	Data slicing requirements . . . . .	62
B.3	Tool builds used for 2013 Q2 data analysis . . . . .	64

# Chapter 1

## Introduction

### 1.1 The definition of offline monitoring

The goal of Offline Monitoring (OLM) is to track the performance of WAAS, establish baseline performance, and characterize anomalous behavior to determine if further investigation is necessary.

### 1.2 Elements of system monitoring

The monitoring addressed in this document can be categorized into five types, namely Integrity, Availability, Continuity, Accuracy and External Monitoring. Each category represents a class of performance that the system exhibits. The intent of this document is to provide a summary of results for several checks of each of the above types in conjunction with condensed plots that show at-a-glance quarterly performance. Each monitoring subsection contains a brief description of the relevant figures and tables along with a reference to a section in Appendix A which contains more detailed (and more numerous) figures and tables.

#### 1.2.1 Integrity

Integrity monitoring is viewed by many to be the most important type since a breach of this class of performance represents a potentially hazardous situation. Loss of Integrity happens when the user's position is not bounded by the calculated Protection Level and the Protection Level is within the Alert Limit. There are monitors in WAAS which internally ensure that these error bounds represent an over-bound of the generated errors. Each monitor has a slightly different method for ensuring integrity, and the individual monitor integrity methodologies are described in their respective monitor subsections.

#### 1.2.2 Availability

Availability Monitoring is straightforward, it evaluates the coverage of WAAS over a defined time period. There are specifics to be defined for this type, namely the Alarm Limits (Vertical and Horizontal) as well as the coverage contour.

### **1.2.3 Continuity**

Continuity monitoring refers to events which can cause a loss of availability but not a breach of integrity. Typically, this assessment looks at monitor trips, setting satellites unusable, or any issue which would cause a loss of service.

### **1.2.4 Accuracy**

Accuracy Monitoring refers to the ability of the WAAS corrections to provide an accurate estimate of the user's position.

### **1.2.5 External monitoring**

External monitoring entails events external to the WAAS, including broadcast ephemerides, plate-tectonic movement (antenna positions), space weather, etc., that can result in anomalous WAAS performance.


# Chapter 2

## Integrity monitoring


### 2.1 Code-noise and multipath

No aggregate failures were found when monitoring the HMI assertion (Appendix A.2) for the second quarter of 2013. There were two failures in the daily sigma overbound. There were no failures for the sigma overbound on any of the aggregate or sliced distribution plots.


For Figures 2.1, 2.2, and 2.3, CNMP passes if the tails (red and blue lines) do not dip below zero on the vertical axis. If a dip below zero occurs close to zero, that event is not considered a failure. For Figure 2.4, if the values go above the marked threshold of 1, that event is a failure. Two CNMP failures occurred during the second quarter of 2013. These were both a result of high values at BRW-A. These failures are being investigated and a full report will close WIPP action item #0193.




**Figure 2.1:** Aggregate CNMP Delay



**Figure 2.2:** Aggregate CNMP IFPR



**Figure 2.3:** Aggregate CNMP RDL1



**Figure 2.4:** Daily GPS CNMP Aggregate zero-centered sigma overbound values

## 2.2 Code-carrier-coherence


The absolute maximum value for the quarter of the CCC metric / MERR value is 0.20 for the GEO SVs and 0.19 for the GPS SVs. Therefore, CCC is extremely well-bounded.

### 2.2.1 CCC integrity tables

Statistic	CRW	CRE	AMR	GPS L1 <sub>agg</sub>	GPS L2 <sub>agg</sub>
mean (m)	0.00	-0.00	0.00	-0.00	-0.00
st dev (m)	0.04	0.03	0.01	0.01	0.01
min (m)	-0.13	-0.13	-0.04	-0.19	-0.19
max (m)	0.20	0.12	0.03	0.19	0.16
abs max (m)	0.20	0.13	0.04	0.19	0.19

**Table 2.1:** CCC integrity statistics (normalized to MERR value)


### 2.2.2 Quarterly time-series plot of CCC GEO metric




**Figure 2.5:** Time-series graph of CCC GEO metrics

## 2.3 Signal Quality Monitoring

All four metrics for GEO satellites fall below the threshold for 2013 Q2. There were no SQM trips for the quarter.



**Figure 2.6:** Time-series graph of GEO SQM metrics




**Figure 2.7:** Time-series graph of GPS SQM max metrics 1-4


## 2.4 Iono threat model

Figure 9.1 on page 41 shows a map of the regions used for threat model analysis.


### 2.4.1 Daily percentage of $\text{Chi}^2$ values $> 1$




**Figure 2.8:** Alaska region daily %  $\text{Chi}^2$  values  $> 1$  taken from ZDC




**Figure 2.9:** Canada region daily %  $\chi^2$  values  $> 1$  taken from ZDC



**Figure 2.10:** Equatorial region daily %  $\chi^2$  values  $> 1$  taken from ZDC





## 2.4.2 Days of interest

The IGP map is now divided into six regions: Alaska, Canada, Equatorial, CONUS, West mid-latitude and East mid-latitude. Figure 9.1 on page 41 shows a map of the regions used for threat model analysis.

Region	CONUS	Alaska	Equatorial	Canada	W. mid-lat	E. mid-lat
Threshold (%)	3.6	8.6	9.4	16.5	4.3	6.8
2013-06-01	7.7939	13.853	15.844		15.457	
2013-06-28						9.8495
2013-06-29	6.1756					9.6875

**Table 2.2:** Days when the % of  $\text{Chi}^2 > 1$  exceed the threshold value

- May 15<sup>th</sup> was flagged, but not iono related
  - “GUS hardware failure of PNE caused missed navigation messages: 5 missed messages at 268354 (2:32), 4 missed messages at 328200 (19:09), 2 missed messages at 328208, and 2 missed messages at 328716. See DR 114 “LPV Service Outage Due to Consecutive SV Alerts on PRN 138” for a more detailed description.” from the PAN report ( $K_p$  was 4).
- June 1<sup>st</sup> and 2<sup>nd</sup>
  - Max  $K_p$  exceeded on June 1<sup>st</sup> ( $K_p = 7$ ) and coverage drop on all four 100% contours on June 2<sup>nd</sup>.
- June 28<sup>th</sup> and June 29<sup>th</sup>
  - Coverage drop in CONUS (99% and 100%) and Alaska (100%) and  $\text{chi}^2$  trip in the Eastern Mid-latitudes for both days, and CONUS  $\text{chi}^2$  trip on the 29<sup>th</sup>.

# Chapter 3

## Availability monitoring

### 3.1 Service volume model

This analysis is under development.

# Chapter 4

## Continuity monitoring

### 4.1 System monitoring trips

Component	ZDC	ZLA	ZTL
BMV	0	0	0
CCC	0	0	0
L1L2	38	37	38
RDM <sub>threshold</sub>	0	0	0
SQM	0	0	0
UPM	0	0	0
WNT 133	0	0	0
WNT 135	0	0	0
WNT 138	0	0	0
WRE <sub>bias</sub>	7	7	7

Table 4.1: System monitoring trips

### 4.2 CCC statistics and monitor trips

During the second quarter of 2013, no CCC monitor trips were observed in the field. Two monitor trips occurred in the prototype runs that were not seen in the field. Anomalies have been created for these events and are currently under investigation.

Date @ time <sub>UTC</sub>	PRN	value	threshold	ZDC	ZLA	ZTL	Anomaly
2013-05-26 @ 02:18:05	138	7.113	7.1	0	0	0	WAAS00120089
2013-06-01 @ 07:51:06	135	2.503	2.5	0	0	0	WAAS00120090

Table 4.2: Reported CCC trips


<b>Statistic</b>	<b>CRW</b>	<b>CRE</b>	<b>AMR</b>	<b>GPS L1<sub>agg</sub></b>	<b>GPS L2<sub>agg</sub></b>
mean (m)	0.01	-0.02	0.06	-0.01	-0.01
st dev (m)	0.49	0.40	0.59	0.14	0.14
min (m)	-4.55	-1.82	-5.55	-2.62	-3.11
max (m)	2.60	7.80	2.90	2.42	2.64
abs max (m)	4.55	7.80	5.55	2.62	3.11

**Table 4.3:** CCC metric statistics (unnormalized)

<b>Statistic</b>	<b>CRW</b>	<b>CRE</b>	<b>AMR</b>	<b>GPS L1<sub>agg</sub></b>	<b>GPS L2<sub>agg</sub></b>
mean (m)	0.00	-0.01	0.01	-0.01	-0.01
st dev (m)	0.19	0.15	0.08	0.05	0.05
min (m)	-0.68	-0.65	-0.50	-0.50	-0.51
max (m)	1.03	1.10	0.40	0.71	0.56
abs max (m)	1.03	1.10	0.50	0.71	0.56

**Table 4.4:** CCC continuity statistics (normalized to trip threshold)

## 4.3 WRE thread switches



**Figure 4.1:** Count of all days with switches


## 4.4 List of missed messages

The missed messages for the second quarter of 2013 are displayed in the histogram in this section. Each bar on the histogram represents one GEO satellite. Brief explanations for the cause of the missed messages are provided. The totals for missed messages per GEO satellite are as follows:

- CRW (PRN-135) - 18
- CRE (PRN-138) - 55
- AMR (PRN-133) - 21

### 4.4.1 CRW (PRN-135) Events

- 2013-06-02 (4 missed messages) - GUS switchover, LTN to primary for scheduled maintenance at APC.
- 2013-06-12 (14 missed messages) - Arc fault on C1 KPA at LTN.




**Figure 4.2:** Time on C thread

#### 4.4.2 CRE (PRN-138) Events

- 2013-04-12 (4 missed messages) - GUS switchover, WBN to primary for scheduled maintenance at BRE.
- 2013-05-02 (1 missed message) - High voltage arc alarm at WBN causing a single missed message.
- 2013-05-15 (29 missed messages) - Carrier frequency deviations caused by PNE at WBN.
- 2013-05-16 (4 missed messages) - GUS switchover, BRE to primary for scheduled maintenance at WBN.
- 2013-05-26 (12 missed messages) - BRE faulted due to C5 upconverter failure.
- 2013-05-30 (5 missed messages) - GUS switchover, BRE to primary for scheduled maintenance at WBN.

#### 4.4.3 AMR (PRN-133) Events

- 2013-04-03 (1 missed message) - Caused by a frequency spike in the uplink signal at HDH.
- 2013-04-17 (6 missed messages) - Caused by a frequency spike in the reference clock at HDH.
- 2013-05-01 (7 missed messages) - GUS switchover, SZP to primary for scheduled maintenance at HDH.
- 2013-06-16 (7 missed messages) - Operator initiated switchover due to KPA alarms at SZP.



**Figure 4.3:** Missed messages

## 4.5 CNMP resets

This section will be added in a future report.

## 4.6 Satellite clock run-off monitoring

There were no clock run-off events in the second quarter of 2013.

# Chapter 5

## Accuracy monitoring

For additional information on WAAS accuracy, see the WAAS PAN Report for 2013Q2:  
<http://www.nstb.tc.faa.gov/REPORTS/waaspan45.pdf>

# Chapter 6

## External monitoring


### 6.1 Antenna phase center positions

Data from 2013-06-09 was used in this survey. The results were compared against Canadian Spatial Reference System Precise Point Positioning (CSRS-PPP). In this comparison, Root Mean Square (RMS) position error for every site was less than three centimeters.

The survey results were also compared to the coordinates in the currently fielded Release 37 software. The surveyed sites were all within seven centimeters of the fielded coordinates, with MTP off by approximately seven centimeters, MMX off by approximately six centimeters, and all other sites off by less than five centimeters. The differences are all within the allowed 10 cm, so no WIPP decision is required.

### 6.2 Ephemerides monitoring

Figures 6.1, 6.2, and 6.3 show the cross-track, in-track, and radial ephemeris deltas between National Geodetic Survey (NGS) precise ephemeris and WAAS Continuously Operating Reference Station (CORS) Receiver INdependent EXchange Format (RINEX) ephemeris.




**Figure 6.1:** Q2 2013 Plot of Cross-Track Ephemeris Deltas between NGS and CORS Ephemeris

GPS PRN	Radial	In-Track	Cross-Track
1	0	0	0
2	0	0	0
3	3	0	0
4	0	0	0
5	0	0	0
6	0	0	0
7	0	0	0
8	9	0	0
9	13	8	0
10	0	0	0
11	0	0	0
12	0	0	0
13	0	0	0
14	0	0	0
15	0	0	0
16	0	0	0
17	0	0	0
18	0	0	0
19	0	0	0
20	0	0	0
21	0	0	0
22	0	0	0
23	0	0	0
24	0	0	0
25	1	0	0
26	29	3	0
27	16	0	0
28	0	0	0
29	0	0	0
30	0	0	0
31	0	0	0
32	1	0	0

**Table 6.1:** Q2 2013 Number of Outliers for each GPS PRN



**Figure 6.2:** Q2 2013 Plot of In-Track Ephemeris Deltas between NGS and CORS Ephemeris



**Figure 6.3:** Q2 2013 Plot of Radial Ephemeris Deltas between NGS and CORS Ephemeris

## 6.3 Space weather monitoring

### 6.3.1 Planetary A-K indices




Figure 6.4: Planetary  $K_p$  values

## 6.4 GEO CCC signal quality analysis (GSQA)

- Data from GCCS GUS Backup sites used for analyses
  - Gaps in data appear on switchover days / maintenance periods
- New feature: ionosphere ramp effects on long-term CCC metrics are mitigated using filtered WAAS IPP data
  - Works well to mitigate macro effects but does not correct sudden changes during storm events
    - \* Generally improves long-term CCC metric, minimal effect on short-term CCC, no effect on CC (cancels)
  - WAAS IPP data smoothed using 1800-sec sliding window filter twice before applying to code and carrier data
    - \* Code must be corrected for local receiver oscillations before applying iono data
- CRE Doppler stayed close to zero for extended periods during the first half of April, causing long-term CCC to exceed spec limit
  - Signal generation issue: CRE SIS did not meet spec on these days
  - GEO stationkeeping is sometimes too stationary (very low Doppler)
  - Root cause: oscillations generated in GUST receiver pseudorange tracking are larger in magnitude and have longer periods when near zero Doppler, corrupting accuracy of SIS generation control loop
    - \* PRN 138 affected more than PRN 135
    - \* Oscillation signatures are PRN code dependent
  - Effect likely can be prevented by applying corrections to primary GUST pseudorange measurements
    - \* Approach can be tested with next generation of GEO satellites
- Geomagnetic storm on June 1<sup>st</sup> caused some metrics for CRW to fail
  - Of all GCCS sites, Napa (APC) was most affected and was Primary for CRW at the time
- Unknown anomaly affected CRW long-term CCC metrics the first week of May
  - Oscillatory multipath-like effect somewhat like GEO crossover event
  - Needs further investigation
- WBN showed instability on/near May 15<sup>th</sup> that caused temporary elevated short-term CCC for CRE
  - PNE suspected

Note that the remaining GSQA figures can be found in the supplemental material in Section 9.6.

		L1 CCC		L5 CCC		CC	
		short-term	long-term	short-term	long-term	short-term	long-term
PRN 135 CRW	max	OK	OK	OK	OK	OK	OK
	mean	OK	OK	OK	OK	OK	OK
PRN 138 CRE	max	OK	> spec	OK	OK	OK	OK
	mean	OK	> spec	OK	OK	OK	OK

<b>OK</b> always below spec limit	<b>&gt; spec</b> sometimes above spec limit	<b>&gt;&gt; spec</b> normally above spec limit
--------------------------------------	--	---

**Table 6.2:** GSQA performance summary

# Chapter 7

## Anomaly investigation

### 7.1 Major Anomalies

#### 1. WRE Bias Trips at MPR

- WRE bias trips occurred at MPR on 2013-05-18, 2013-05-20 and 2013-06-14 and are suspected to be attributable to faulty hardware. No RFI was detected. See anomaly numbers WAAS00119801 and WAAS00119660. Time and dates of the WRE bias trips are listed below:
  - (a) 1052929392 05/18/2013 16:22:56
  - (b) 1053095826 05/20/2013 14:36:50
  - (c) 1053095987 05/20/2013 14:39:31
  - (d) 1055252264 06/14/2013 13:37:28
  - (e) 1055252497 06/14/2013 13:41:21

#### 2. Instability on the L1 loopback path at HDH GUS site

- On 2013-04-03 there was a missed message caused by a frequency jump on L1 while HDH was primary. This suggested an issue with the C1 upconverter or possibly a cable/connector issue. On 2013-05-02 the C1 upconverter was replaced. Intermittent Doppler spikes were observed shortly after the replacement of the C1 upconverter. Further troubleshooting efforts will be attempted in order to isolate the problem. See anomaly numbers WAAS00199597 and WAAS00007979 for more details.

# Chapter 8

## Materials and methods

### 8.1 Code-carrier-coherence

Anik, Galaxy 15, AMR and all GPS satellites are monitored for CCC trips. All CCC monitor trips are investigated whenever a trip occurs to determine the cause. Data sources used in correlation and analysis include:

- CCC test statistic
- UDRE threshold value
- Code Minus Carrier corrected for Iono (CMCI) measurements from NETS SQA
- WAAS Iono calculation
- L1/L5 Iono GEO Uplink Subsystem Type 1 (GUST) calculation
- published planetary  $K_2$  and  $A_2$  values
- $\text{Chi}^2$  values

### 8.2 Antenna positioning

Accurate antenna positions are needed for WAAS or any Differential Global Positioning System (DGPS) application. The positions must be updated to correct for time dependent processes like tectonic plate movement and subsidence. They also need to be updated for events which shift the position of the antennas. These might include seismic events or maintenance. Antenna position results from OLM will be used to determine if the WAAS antenna coordinates require an update.

The WIPP reviews antenna position changes based on how much the antenna moves. If the antenna moves more than ten centimeters, the WIPP should review. If an antenna moves more than 25 centimeters, the WIPP must review. Mexico city is a special case due to the rapid subsidence at that site. It is allowed 25 centimeters before review.

The NGS's suite of survey software (PAGE-NT) is used to conduct a survey with WAAS site data from the current quarter. These results are compared against CSRS-PPP using the same input data.

## 8.3 Satellite clock Run-off monitoring approach

A GPS clock run-off event is typically correlated with a WAAS fast correction that exceeds 256 meters. When this occurs, the satellite is set to Do Not Use until the correction reaches a reasonable size. A real clock-runoff occurs when these events happen at times that the GPS satellite is in a healthy status, in view of WAAS, and there is no Notice Advisory to NAVigation System with Time And Range (NAVSTAR) Users (NANU) in effect for the specific GPS SV.

The approach to monitor for GPS clock run-off events is to collect quarterly data for SV health from CORS RINEX files, NANUs from the US Coast Guard, and Fast Correction and User Domain Range Error Index (UDREI) data from WAAS User Message (WUM)s. Once collected, the data is analyzed for the entire quarter.

## 8.4 Ephemerides Monitoring Approach

The difference between the precise GPS orbits provided by the NGS and the ephemeris derived from the CORS RINEX files for all available sites is computed and analyzed. A voting algorithm is employed to select the best set of ephemerides from the CORs data. Outliers are analyzed and tabulated.

## 8.5 Iono threat model monitoring approach

Monitor the percentage of Chi<sup>2</sup> values > than 1 each day for the six regions (see 2.4.2) and determine whether the threshold has been reached. The regions and thresholds are:

<b>Region</b>	<b>Threshold (%)</b>
Alaska	8.6
Canada	16.5
Equatorial	9.4
CONUS	3.6
W Mid-latitude	4.3
E Mid-latitude	6.8

**Table 8.1:** Threat model regions and threshold settings

## 8.6 Code-noise and multipath

To monitor the CNMP HMI assertion (appendix A.2), we check the bounding for three statistics, L1, IFPR, and Delay. The equations used to determine a passing or failing grade for the distribution plots are in Appendix 9.3.2. The zero-centered sigma overbound plots are considered to be passing if the value is less than one, which is marked in the plots.

## 8.7 GEO CCC signal quality analysis (GSQA)

### 8.7.1 Data

- Data from GCCS GUS Backup sites used for analyses

### 8.7.2 Methods

- Graphs of data were generated using MATLAB

# Chapter 9

## Supplemental material

### 9.1 Iono threat model defined regions

Six regions (Alaska, Canada, CONUS, Equatorial, East mid-latitude and West mid-latitude) define the  $\text{Chi}^2$  statistical analysis and shown below:




Figure 9.1:  $\text{Chi}^2$  region map

### 9.2 Code-noise and multi path

#### 9.2.1 Analysis of poor performing sites

Table 9.1 contains information on the worst performing sites of the quarter. Table 9.1 is generated by using the method described in Section A.1.5 of the HMI document. Three metrics are considered including the absolute mean, standard deviation and the absolute maximum of the normalized residual distributions sliced by WRE for IFPR CNMP, delay CNMP, RDL1 CNMP and RDL2 CNMP. These twelve metrics are then combined into one ranking metric. Each of the twelve metrics is normalized to a number between 0 - 1 and then those are sorted by WRE and averaged over the twelve metrics. The 10 worst WREs, as determined by the combined metric, are listed in table 9.1.

Station		RDL1				IFPR				Delay			
#	Name	$\mu$	$\sigma$	$ max $	sigobz	$\mu$	$\sigma$	$ max $	sigobz	$\mu$	$\sigma$	$ max $	sigobz
29	ZHU B	-0.02	0.431	3.10	0.740	0.05	0.466	3.70	0.887	-0.08	0.475	3.65	0.878
30	ZHU C	0.05	0.442	2.85	0.690	0.07	0.419	2.55	0.623	-0.07	0.408	2.40	0.611
63	ZOB C	-0.01	0.257	1.85	0.432	0.07	0.302	2.25	0.513	-0.10	0.332	2.20	0.505
2	BIL B	-0.10	0.291	2.10	0.493	-0.07	0.296	2.00	0.495	0.06	0.321	1.85	0.482
38	ZKC B	-0.04	0.345	2.60	0.648	0.04	0.335	3.20	0.765	-0.07	0.328	3.30	0.779
21	ZDV C	-0.05	0.342	2.85	0.688	0.00	0.354	2.55	0.613	-0.03	0.367	2.30	0.561
94	MPR A	0.07	0.279	2.30	0.495	0.09	0.278	2.00	0.474	-0.09	0.278	2.20	0.568
108	MTP C	-0.03	0.364	2.55	0.572	0.02	0.331	2.75	0.615	-0.05	0.323	2.60	0.581
28	ZHU A	-0.05	0.377	3.00	0.706	-0.03	0.359	2.20	0.499	0.02	0.367	2.00	0.468
39	ZKC C	-0.01	0.357	2.30	0.542	0.02	0.356	2.05	0.501	-0.04	0.363	2.50	0.573

**Table 9.1:** Poor performing WREs for CNMP

## 9.3 Equations

### 9.3.1 Code-carrier-coherence

$$ccc_y^j = \frac{\sum_i \left[ \frac{\mu_{y,cnmp,i}^j}{(\sigma_{y,cnmp,i}^j)^2} \right]}{\sum_i [(\sigma_{y,cnmp,i}^j)^{-2}]}$$

where:

$\mu_{y,cnmp,i}^j$  is the instantaneous difference of the code measurements vs. the adjusted carrier phase for SV j as measured by WRE i for each  $y \in L1, L2$ ,

$\sigma_{y,cnmp,i}^j$  is the standard deviation of the CNMP measurements for SV j as measured by WRE i for each  $y \in L1, L2$ ,

$|ccc_y^j|$  is the carrier-smoothed, CCC monitor output statistic generated by a first-order smoothing filter with  $\tau_c = 25$  seconds.

The probability of the CCC metric exceeding the Maximum Error Range Residual (MERR) is:

$$P_{HMI} = \Phi^R \left( \frac{\text{MERR} - \text{MDE}_{\text{monitor}}}{\sqrt{\sigma_{udre,nominal}^2 + F_{PP}^2 \sigma_{uive,nominal}^2}} \right)$$

$$\text{MERR} = 5.33 \sqrt{\sigma_{udre}^2 + (F_{pp} \sigma_{uive})^2}$$

$$\text{MDE} = T_{ccc} + k_{ma} \sigma_{test}$$

$$(\Phi^R)^{-1}(P_{md}) = k_{md}$$

### 9.3.2 Code-noise and multipath

The Cumulative Density Function (CDF) is defined as:

$$\Phi^R(x) = \frac{1}{\sqrt{2\pi}} \int_x^\infty e^{-\frac{t^2}{2}} dt$$

$$\Delta(x) = \begin{cases} \frac{\Phi_{theory}^R(x) - \Phi_{data}^R(x)}{\Phi_{theory}^R(x)} & \text{if } x \geq 0 \\ \frac{[1 - \Phi_{theory}^R(x)] - [1 - \Phi_{data}^R(x)]}{1 - \Phi_{theory}^R(x)} & \text{if } x < 0 \end{cases}$$

CNMP passes when the following condition is met:

$$\Delta(x) > 0 \text{ for all } |x| > 0.25$$

## 9.4 Tables

### 9.4.1 Code-carrier-coherence

UDREI	$\tau_{ccc,gps}$	$\tau_{ccc,geo}$
5	1.94	0
6	1.99	0
7	3.00	0
8	3.88	0
9	4.00	0
10	6.00	2.5
11	12.0	3.0
12	40.0	7.1
13	100	20

**Table 9.2:** CCC trip thresholds per UDRE index

## 9.4.2 WRE listing

WRS Index	Location	Symbol
0	Billings, Montana	BIL
1	Albuquerque, New Mexico	ZAB
2	Anchorage, Alaska	ZAN
3	Chicago, Illinois	ZAU
4	Boston, Massachusetts	ZBW
5	Washington, DC	ZDC
6	Denver, Colorado	ZDV
7	Fort Worth, Texas	ZFW
8	Honolulu, Hawaii	HNL
9	Houston, Texas	ZHU
10	Cold Bay, Alaska	CDB
11	Jacksonville, Florida	ZJX
12	Kansas City, Kansas	ZKC
13	Los Angeles, California	ZLA
14	Salt Lake City, Utah	ZLC
15	Miami, Florida	ZMA
16	Memphis, Tennessee	ZME
17	Minneapolis, Minnesota	ZMP
18	New York, New York	ZNY
19	Oakland, California	ZOA
20	Cleveland, Ohio	ZOB
21	Seattle, Washington	ZSE
22	San Juan, Puerto Rico	ZSU
23	Atlanta, Georgia	ZTL
24	Juneau, Alaska	JNU
25	Barrow, Alaska	BRW
26	Bethel, Alaska	BET
27	Fairbanks, Alaska	FAI
28	Kotzebue, Alaska	OTZ
29	Mérida, Yucatán	MMD/Q9C
30	Mexico City	MMX/Q9A
31	Puerto Vallarta, Jalisco	MPR/Q9B
32	Gander, Newfoundland and Labrador	YQX
33	Goose Bay, Newfoundland and Labrador	YYR
34	San José del Cabo, Baja California Sur	MSD/Q9E
35	Tapachula, Chiapas	MTP/Q9D
36	Iqaluit, Nunavut	YFB
37	Winnipeg, Manitoba	YWG

**Table 9.3:** WRE listing

### 9.4.3 Space vehicle designators

SV	Common name	Int. designator	Owner	Launch date
CRE	Anik F1-R	2005-036A	Telesat	2005-09-08
CRW	Galaxy 15 or PanAm	2005-041A	Intelsat	2005-10-13
AMR	Inmarsat 4-F3 or AMR	2008-039A	Inmarsat	2008-08-18

**Table 9.4:** GEO satellite information I

SV	PRN	GUST sites	Position	Period	Apogee	Perigee	RCS
CRE	PRN 138	WBN BRE	$107.3 \pm 0.01^\circ \text{W}$	1436.09min	35796m	35777m	$5.0139\text{m}^2$
CRW	PRN 135	LTN APC	$133.0 \pm 0.01^\circ \text{W}$	1436.08min	35798m	35974m	$3.9811\text{m}^2$
AMR	PRN 133	SZP HDH	$98.0 \pm 3.01^\circ \text{W}$	1436.11min	35776m	35776m	$2.1948\text{m}^2$


**Table 9.5:** GEO satellite information II

## 9.5 References


WAAS CDRL A014-011 *Algorithm Contribution to HMI for WAAS*

## 9.6 GEO CCC signal quality analysis (GSQA)


Note: missing values indicate days with switchovers or incomplete data




**Figure 9.2:** Long-term fractional coherence (CC) for PRN 135




**Figure 9.3:** Short-term fractional coherence (CC) for PRN 135




**Figure 9.4:** Long-term fractional coherence (CC) for PRN 138




**Figure 9.5:** Short-term fractional coherence (CC) for PRN 138




**Figure 9.6:** Long-term code-carrier coherence (CCC) for PRN 135



**Figure 9.7:** Short-term fractional coherence (CC) for PRN 135



**Figure 9.8:** Long-term code-carrier coherence (CCC) for PRN 138



**Figure 9.9:** Short-term fractional coherence (CC) for PRN 138

## 9.7 L1L2 bias levels

### 9.7.1 Satellites from CP1




Figure 9.10: L1L2 bias for all PRNs from CP1

## 9.7.2 Satellites from CP2




Figure 9.11: L1L2 bias for all PRNs from CP2

### 9.7.3 WREs from CP1




Figure 9.12: L1l2 bias for all WREs from CP1

## 9.7.4 WREs from CP2




Figure 9.13: L1l2 bias for all WREs from CP2

# Appendix A

## Assertions

### A.1 Code-carrier-coherence

The *a priori* probability of a CCC failure is less than  $1e^{-4}$  per set of satellites in view per hour for GPS satellites and  $1.14e^{-4}$  for GEO satellites.

### A.2 Code-noise and multipath

The HMI document for CNMP states:

The Code Noise and Multipath (CNMP) error bound is sufficiently conservative such that the error in linear combinations of L1 and L2 measurements is overbounded by a Gaussian distribution with a sigma described by the Root Sum Square (RSS) of L1 and L2 CNMP error bounds except for biases, which are handled separately.

### A.3 Antenna positioning

The Root Sum Square (RSS) position error for each WAAS reference station antenna is 10 centimeters or less when measured relative to the International Terrestrial Reference Frame (ITRF) datum for any given epoch (Mexico City is allowed 25 centimeters). The ITRF datum version (realization) is the one consistent with the World Geodetic System's latest reference coordinate system (WGS-84) and also used for positions of the Global Positioning System (GPS) Operational Control Segment monitoring stations.

### A.4 Iono threat model

The values of  $\sigma_{\text{decorr\_undersampled}}$  and  $\epsilon_{\text{iono}}$  adequately protect against worst case undersampled ionosphere over the life of any ionospheric correction message, when the storm detectors have not tripped.

### A.5 Satellite Clock Runoff

The *a priori* probability of a GPS satellite failure resulting in a rapid change in the GPS clock correction is less than  $1.0 \times 10^{-4}$  per satellite.

# Appendix B

## Coding standards and guidelines

### B.1 Introduction

The standards and guidelines for the Offline Monitoring effort are recorded here. “Standards” represent a “rule” that is assumed to be “enforceable”, that is, it has been agreed to by the stakeholders and recorded as official. PCRs can (but not necessarily will) be blocked due to lack of upholding a standard. Furthermore, standards can certainly have exceptions, but these are dealt with on a case-by-case basis and recorded as such. “Guidelines”, on the other-hand, are not enforceable. Guidelines represent good ideas and common engineering practices across the group. Program Change Request (PCR)s cannot be blocked as a result of not following a guideline.

Transitioning from a guideline to a standard is a done on a case-by-case basis. While there is no hard and fast rule for how this is done, the steps for this usually contain an initial agreement by the stakeholders (which included management and engineers) that a standard ought to be adopted, a resource (with associated level of effort) assigned, and an initial assessment as to how much work is involved (estimated end date, etc). The process of transitioning from a guideline to a standard is known as refactoring, and the practice is encouraged as long as stakeholder buy-in is considered at each step.

The standards and guidelines are differentiated by the words “shall” and “should”.

### B.2 Integrity standards for MATLAB

The integrity standards for MatLab were developed during the WAAS FLP Release 6/7 time frame. These standards represent rules that, if broken, could lead to incorrect or erroneous results (not necessarily a tool crash but actual incorrect output). These are documented in the WAAS HMI document (in section 4.3.3 of that document) and are repeated here in their condensed form. More detail can be found in the WAAS HMI document. Note that these standards are enforced by use of the CD\_STD\_CHK tool which parses the files/scripts line by line checking for breaches.

- MATLAB Calling Ambiguity:
  - Ensure that no MATLAB keywords are used as function names.
  - Use functions, not scripts.
  - Function name and filename being the same is required.
  - One function per file required.
  - Functions should not be influenced by anything other than inputs:

- No **global** variables.
- No **persistent** variables.
- MATLAB Functionality Ambiguity:
  - The **squeeze** function shall not be used.
- Windows Ambiguity:
  - The **exist** function shall not be used.
- Coding Clarity:
  - The **eval** command shall not be used.
- Consistency Check:
  - OSP consistency must be addressed.
  - Critical parameters need to not be hardcoded in the tools
- Repeatability:
  - The actual scripts that were used to generate the data, tables and plots need to be captured along with the outputs, as well as a mapping to the actual data set used.

## B.3 HMI/OLM coding standards

Along with the Integrity standards described in section 9.4.1, there exist several “Offline Monitoring” coding standards. These are coding standards which are attached to the running of the Offline Monitoring code and which have been identified as required for the processing of the offline monitoring data. Currently, there are five standards:

- All open files shall be closed
  - This requirement should be applied over all tools for all Offline Monitoring scripts. This requirement is simple, as it just requires that any file which is opened be appropriately closed in the same script that opens it.
- In MatLab, the **figure** command needs to always have a file ID associated with the open figure
  - The MatLab coding language allows the user to create figures without assigning a file id variable. Closing the specific figure is then impossible in general, and the figure must be closed either by keeping track of the current figure ID, or by applying the **close all** command. Neither of these is desired, and as such, each figure must have a unique file ID in memory.
- In MatLab, the **close all** command shall not be used.
  - The **close all** command is issued to close all figures with or without a file ID. As standards are in place to assign a file ID for all figures, this line of code is unnecessary and should not be used.

- All open figures should have the option to be closed
  - The MatLab tools should not leave open figures after the analysis is run (by default). For particular tools, it may be desirable to keep the plots up on the screen, but the option to close them should be implemented
- Use `cs_saveplot` for saving plots in MatLab
  - The `cs_saveplot` function is a common script which saves figures to results directories. There are several options when saving a plot, and using this function allows one place to modify the saving requirements.

## B.4 File naming conventions

While no complete convention exists, there are standard “pieces” which shall be enforced for the OLM effort. These refer to the labels inside the actual name of the tool which refer to information in the data file. The requirements are listed below:

- Filenames shall be named using a prefix, followed by an “\_”, then the ISO8601 date in the form of YYYY-MM-DD, followed by a “.” and the extension.
- Filenames shall use lowercase letters, integers, underscores and dashes.
- There shall be no more than one “.” in a file name
- Text files shall end with the suffix “.txt”
- Binary files shall end with the suffix “.bin”
- Files which contain data for a particular PRN shall have a six-character label of the form “prnDDD” where DDD are the three digits referring to the PRN number. PRNs less than 100 shall have a leading zero, and PRNs less than 10 shall have two leading zeros.
- Files which contain data for a particular WRE shall have a six-character label of the form “wreDDD” where DDD are the three digits referring to the WRE number. WREs less than 100 shall have a leading zero, and WREs less than 10 shall have two leading zeros. Also note that WREs start counting at 0, so for a 38-station system, the WRE number range from 0 to 113.
- Files which contain data for a particular UDREI shall have a seven-character label of the form “udreidd” where DD are the two digits referring to the UDREI. UDREIs less than 10 shall have a leading zero. Also note that UDREIs start counting at 0, so UDREIs range from 0 to 15.
- Files which contain data for a particular GIVEI shall have a seven-character label of the form “giveidd” where DD are the two digits referring to the GIVE index. GIVEIs less than 10 shall have a leading zero. Also note that GIVEIs start counting at 0, so GIVEIs range from 0 to 15.

## B.5 OLM file formats

Standard file formats have been defined for four types of files, listed below. These represent standards, and are enforceable requirements.

## B.5.1 Histogram files

The number of columns in a histogram file shall be one more than the sum of the number of slices. For example, if a histogram file contained an aggregate histogram, slices by UDREI and slices by PRN (both GEO and GPS), there would be  $1+1+16+44 = 62$  columns. The first column is the bins, the second column is the aggregate, columns 3 through 18 are the 16 UDRE slices (with columns 17 and 18 being NM and DU), columns 19 through 50 are the 32 GPS PRNs, columns 51 through 60 are the GEO PRNs (which the last five being held in reserve), column 61 is the aggregate GPS histogram and column 62 is the aggregate GEO histogram.

- Histogram files are stored as raw counts, not probabilities and the bins are recorded as bin centers.
- Histogram files can be daily or compiled into a report.
- The histogram file shall have a header which has column headings lined up with the columns of the data.

## B.5.2 Statistics files

Each statistic in the statistics file shall be defined to be able to be computed using bins (either centers or edges) and the raw counts, and each column in the histogram file shall have all statistics computed for it. Thus, the dimensions of a statistics file shall be as such.

- The number of rows is the same as the number of statistics
- The number of columns shall be the same as the number of slices

In order to account for the column of bins, a statistic index is placed there, so that each column in a histogram file corresponds to the same column in the statistic file. There are currently fifteen descriptive statistics computed for each histogram file:

1. Counts
2. Mean
3. Standard Deviation
4. Minimum
5. Maximum
6. Absolute Maximum
7. Sigma Over-bound (Zero-centered)
8. Sigma Over-bound (Mean-centered)
9. 1st Quartile
10. Median (2nd Quartile)
11. 3rd Quartile

12. Mean of Absolute Value
13. Standard Deviation of Absolute Value
14. RMS
15. Variance

The statistics file shall have a header which has column headings lined up with the columns of the data, as well as the list of statistics represented in the file. Statistics files can be daily or compiled into a report.

### **B.5.3 Time-series files**

Time series files represent a quantity which evolves over time. These can be any quantity, but currently only satellite quantities are created. Thus, the file naming convention for PRN (described in 4.4.2) are utilized.

The time series files have as the first three columns three different representation of time. The first is WAAS time, the second is Universal Time, Coordinated (UTC) in ISO-8601 format (HHMMSS) and the third is seconds in the day. After the first three columns, more columns can be added. The intent of the time series file is to have all of the data which a plot would require in the subsequent columns. Time series files are only attached to daily quantities, but several time series files could be concatenated together to create a multi-day file (and plot).

### **B.5.4 Quantity files**

Quantity files contain two dimensional slices of a particular quantity. For example, creating a UDREI/GPS PRN slice for the absolute maximum of the CCC metric would allow a user to see which satellite have issues at which UDREIs. As both dimensions are used, only one statistic per file can be represented. Quantity files are currently only daily files, but they could be created for a compiled data for some statistics.

### **B.5.5 Quarterly files**

Quarterly files are the files which are plotted over the period of the quarter. Thus, the first column is the number of the day in the quarter and the second (and subsequent) columns are data to be plotted. The data set can be customized for the particular plot.

## **B.6 Histogram slicing and bin requirements**

For many of the analyses, histograms are used to show compliance to particular requirements. As there is inherent averaging in creating an aggregate histogram, the concept of slicing was introduced early in the WAAS analysis process. This requires that data from (potentially) different error sources are not averaged into a single histogram, but are examined separately. In order to compile results across multiple days (and data sets), both the bin centers and the number of columns for each type of slice needs to be fixed. Modifying these requirements at a later date would make long term trending difficult, if not impossible.

The table below shows the bin requirements for the data files which are to be histogrammed by one or more of the Offline Monitoring analyses. Note that the minimum and maximum data cutoffs are defined to be the bin EDGES, not the bin centers. Thus, the bin centers are in between the defined edges. The

Data description	Filename	Data min	Bin width	Data max	Units
Raw CCC metric (L1 and L2)	qstats*	-8.0	0.01	8.0	meters
CCC metrics / trip threshold	qstats*	-3.0	0.01	3.0	none
CCC metrics / MERR value	qstats*	-2.0	0.001	2	none
Max SQM metric	sqm_reduced*	0	0.001	2.0	none

**Table B.1:** Data histogram bin requirements

table below shows the slicing requirements. These include the number of columns and designations for each type of slice.

Slice description	# of columns	Column description
Aggregate	1	This is the histogram of the entire metric. There is always one column, no more.
UDRE index	16	Columns 1-14 represent the data associated with a UDREI of one less than the column, i.e., UDREIs of 0-13. The last two columns represent satellites which are NM (not monitored) and DU (don't use) respectively.
PRN	44	The PRN slices come in a few sets. The first set is the first 32 PRNs. The second set is 10 columns devoted to past, current and future GEOs. The first five GEO columns are the GEO PRNS of 122, 133, 134, 135, and 138. The next five columns are reserved for future GEO PRNS. Finally, the last two columns are the aggregate of the GPS and GEO data respectively.

**Table B.2:** Data slicing requirements

## B.7 OLM process and procedures

### B.7.1 Schedule and meetings

The OLM group will meet approximately twice a quarter. One set of meetings is to be set for the first week of the new quarter to go over plans for that quarter. The second set of meetings is to be set for shortly before the WIPP. For both meetings, the general purpose is to plan for the next WIPP or the next OLM report, as the case may be. At the meetings, task lists with priorities and resources are created, to be reviewed at the next set of meetings. The OLM document is released once a quarter. The analyses should be running during the quarter, and should be being reviewed on a periodic basis. Once the quarter ends, three dates are pertinent.

- Two weeks after the quarter ends - All analyses complete

- Four weeks after the quarter ends - Draft document released
- Six weeks after the quarter ends - Final document completed

## B.7.2 Data processing

The data processing strategy for the OLM document is to currently run the safety processor prototype on blocks of snoop files, approximately one week long. Along with the snoop files, information from the Field SP logs is used in conjunction with the FUNCTION\_CNMP\_SEED flag in the prototype to seed the prototype with CNMP monitor levels. The blocks are then run in succession to create a “quarter’s” worth of data, which spans the three months of the quarter in question. The blocks of data are usually a week long, but due to data issues, as well as week VS month cutoff issues, the lengths of the individual blocks may vary.

Standard processing is applied across the analyses for the individual days. This includes the creation of histogram files, histogram statistics files, time series files, and two dimensional quantity files. There are associated plots as well for each of the above mentioned plots. In addition to the standard processing, analyses specific to the tool are also run for each day. In this way, analysis-specific data reduction and results are generated on a daily basis.

Once the daily analyses have been run, the results are compiled into a “report” directory. This includes the accumulation of histogram data, and the plotting of statistics across the quarter.

## B.7.3 Tool strategy

Tool builds created at both Safety and Operations Support (SOS) and Sequoia Research Corporation (SRC) are valid, and need to have proper versioning attached to them. All of the results from a single quarter should come from one version of a tool, and this version should be recorded in the OLM document.

Both regression testing and coding standards checking are as automated as possible, and both have tools associated with them. For the regression testing, the “reg” MatLab tool has been created. This tool is stored in the OLM repository, and runs the regression tests for the MatLab tools in an automated way (from `reg_go.m`). The coding standards are checked via the `CODE_STD_CHK` tool. There is one standard which checks that all of the scripts are in the top-level directory, followed by the ten integrity standards, followed again by the five OLM coding standards.

As is often the case, tools (old and new) do not comply with the coding standard at the outset. As such, a “refactoring” approach is adopted. By “refactoring”, it is meant that some way to assess the level of non-compliance is required (either by manual review or via automation) before work commences on fixing the issue across the tool set. Once this is assessed, the work commences as is best seen fit by the group, and the standard is enforced for future tools.

The SQM tool is the only tool which does not have all of its scripts in the top level folder. Thus, it is not possible to assess any other issues until that first issue has been worked. For the other tools, the ten integrity standards are all met, and then several of the OLM standards are in a state of non-compliance. As of the writing of this document, PCRs are in place to fix the issues. Note that two other standards (which have to do with Single Line of Code (SLOC) count and complexity) are also listed.

## B.7.4 Tool builds

The following table captures the tool versions used to generate the data in this document.

<b>Prototype</b>	
W3SP_121221_seed_src_wfo_r3c	All dates
<b>HMI Tools</b>	
OLM_TOOLS_318i_r791	All dates
OLM_TOOLS_318j_r1028	CNMP for all dates
<b>Antenna Positions</b>	
PAGE-NT pnt6k	All dates

**Table B.3:** Tool builds used for 2013 Q2 data analysis

# Appendix C

## Acronyms and abbreviations

<b>CCC</b> Code-Carrier Coherence.....	1
<b>CDF</b> Cumulative Density Function .....	43
<b>CMCI</b> Code Minus Carrier corrected for Iono.....	38
<b>CNMP</b> Code-Noise and Multipath.....	1
<b>CORS</b> WAAS Continuously Operating Reference Station .....	29
<b>CSRS-PPP</b> Canadian Spatial Reference System Precise Point Positioning .....	29
<b>DGPS</b> Differential Global Positioning System.....	38
<b>FAA</b> Federal Aviation Administration .....	2
<b>GEO</b> Geosynchronous Earth Orbit.....	1
<b>GPS</b> Global Positioning System .....	56
<b>GUST</b> GEO Uplink Subsystem Type 1 .....	38
<b>HMI</b> Hazardous Misleading Information .....	1
<b>IFPR</b> Ionospheric Free PseudoRange.....	6
<b>ITRF</b> International Terrestrial Reference Frame.....	56
<b>MERR</b> Maximum Error Range Residual.....	43
<b>MMAC</b> Mike Monroney Aeronautical Center .....	1
<b>NANU</b> Notice Advisory to NAVSTAR Users.....	39
<b>NAVSTAR</b> NAVigation System with Time And Range.....	39
<b>NGS</b> National Geodetic Survey .....	29
<b>OLM</b> Offline Monitoring .....	8
<b>PAGE-NT</b> The NGS's suite of survey software.....	38
<b>PCR</b> Program Change Request .....	57
<b>RDL1</b> Range Domain for the L1 frequency.....	6
<b>RINEX</b> Receiver INdependent EXchange Format .....	29
<b>RMS</b> Root Mean Square .....	29
<b>RSS</b> Root Sum Square .....	56

**SLOC** Single Line of Code.....63

**SOS** Safety and Operations Support.....63

**SQM** Signal Quality Monitoring.....1

**SRC** Sequoia Research Corporation.....63

**UDREI** User Domain Range Error Index ..... 39

**UTC** Universal Time, Coordinated ..... 61

**WAAS** Wide-Area Augmentation System.....1

**WGS-84** World Geodetic System’s latest reference coordinate system..... 56

**WIPP** WAAS Integrity Performance Panel.....2

**WRS** Wide-area Reference Station.....1

**WSF** WAAS Support Facility.....1

**WUM** WAAS User Message.....39